



Schmooze Com Inc.

How To Find The IP Address

Quick Steps

1. Press the "Menu" button.



2. Scroll down to the "Status" option and press the "Select" button.



3. Scroll down to the "Platform" option and press the "Select" button.



4. Scroll down to the "Phone" option and press the "Select" button.



5. Use the up/down arrow key to scroll through the list of information to see the IP Address.

		VVX-150	0 242
Phone		2000000	VVX-15
DHCP: Enabled			
IP: 10.4.0.169			
BootBlock: 3.0.1 (17960-001)			
Updater: 5.0.3.1966			
	XXX	XXXX	

How To Find The MAC Address

Quick Steps

1. Press the "Menu" button.



2. Scroll down to the "Status" option and press the "Select" button.



3. Scroll down to the "Network" option and press the "Select" button.



4. Scroll down to the "Ethernet" option and press the "Select" button.



5. Use the up/down arrow key to scroll through the list of information to see the MAC Address.



How To Set The Configuration Server

Quick Steps

1. Press the "Menu" button.



2. Scroll down to the "Settings" option and press the "Select" button.



3. Scroll down to the "Advanced" option and press the "Select" button.



4. Enter the admin password and press the "Enter" button. Default factory password is 456.



5. Scroll down to the "Admin Settings" option and press the "Select" button.



6. Scroll down to the "Network Configuration" option and press the "Select" button.

	VV.	10:41 AM ¹ Thu ¹ X-1500 24
Administration Settings		VVX-150
1 Network Configuration		
2 Line Configuration		
3 Call Server Configuration		
4 TLS Security		

7. Scroll down to the "Server Menu" option and press the "Select" button.

	10:44 / VVX-150	AM 24
Provisioning Server		VVX-1500
Server Type:	Trivial FTP	
Server Address:	10.10.0.1	
Server User:	PlcmSpIp	
	Back Select	<u>ن</u>

8. Pick the Server Type such as TFTP and set the Server Address and press the "Select" button. The Server address would be the IP address of your PBX.

	12:43 PM VVX-1500	24
Provisioning Server		WX-1500
DHCP Menu		
Server Type:	Trivial FTP	
Server Address:	10.10.0.1	
Server User:	PlcmSpIp	
1991993	XXXXXXXXXX	
	Back Select	

How To Factory Default

Quick Steps

1. Press the "Menu" button.



2. Scroll down to the "Settings" option and press the "Select" button.



3. Scroll down to the "Advanced" option and press the "Select" button.



4. Enter the admin password and press the "Enter" button. Default factory password is 456.



5. Scroll down to the "Admin Settings" option and press the "Select button".



6. Scroll down to the "Reset to Default" option and press the "Select" button.

10:47 AM VVX-1500	24_
Administration Settings	VVX-1500
3 Call Server Configuration	
4 TLS Security	
S Reset to Defaults	
6 Change Admin Password	
Back Select	ि ि

7. Scroll down to the "Format File System" option and press the "Select" button.





(920) 886-8130

http://schmoozecom.com